

# Technical Data Sheet

## Regenerat Freight Secure Premium

High-grade recycled rubber anti-slip mat (granules bonded with polyurethane)  
lightly coloured to protect the load of black abrasion standard material does not provide  
Maximum load: 270t/m<sup>2</sup> 8 mm thickness

### Technical Data\*:

Colour	multicolored
Density:	1,05
Tensile strength:	min.0,6 N/ mm <sup>2</sup>
Elongation:	min 60 %
Temperature range:	-30° - +100° C

\*approximately

### Chemical Resistance:

Oil resistance:	-
Bezine resistance:	-
Acid resistance:	<b>0</b>
Strong bases:	<b>0</b>
Ozone - and weather resistance:	+
Abrasion:	-

### Recommendation:

### Available Dimmensions:

Thickness	Width/Length:	Format:
03-10 mm	1,25 x 10 m	roll

### General Information:

Surface grain-textured

Legend for recommendation of chemical resistance:  
++ = excellent; + = acceptable; 0 = moderately; - = non resistant

\*\* The information, figures, test values and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operation conditions influence the application of each product, the information supplied can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether specified properties of our products are sufficient for the intended use. The use of our products is at the user's own risk. We do not have any influence concerning the application and individual usage.