

# Technical Data Sheet

## Soft PVC Sheet

Translucent with cut edges

**Technical Data\*:**

Colour: translucent  
 Shore: 80 Shore  
 Density: 1,6 kg/ m<sup>2</sup>  
 Tensile strength: 16 N/ mm<sup>2</sup>  
 Elongation: 340%  
 Temperature range: -15° - +150° C

\*approximately

**Chemical Resistance:**

Oil resistance: -  
 Benzene resistance: -  
 Acid resistance: -  
 Strong bases: -  
 Ozone - and weather resistance: ++  
 Abrasion: -

**Recommendation:**

**Available Dimensions:**

Thickness	Width/Length:	Format:
01-02 mm	1,2 x 20 m	roll
03-10 mm	1,2 x 10 m	

**General Information:**

Available without plies  
 Both sides smooth

Legend for recommendation of chemical resistance:

++ = excellent; + = acceptable; 0 = moderately; - = non resistant

\*\* The information, figures, test values and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operation conditions influence the application of each product, the information supplied can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether specified properties of our products are sufficient for the intended use. The use of our products is at the user's own risk. We do not have any influence concerning the application and individual usage.