

Technical Data Sheet

Regenerat Freight Secure Premium

High-grade recycled rubber anti-slip mat (granules bonded with polyurethane)
lightly coloured to protect the load of black abrasion standard material does not provide
Maximum load: 270t/m² 8 mm thickness

Technical Data*:

Colour: multicolored
Density: 1,05
Tensile strength: min.0,6 N/ mm²
Elongation: min 60 %
Temperature range: -30° - +100° C

*approximately

Chemical Resistance:

Oil resistance: -
Benzene resistance: -
Acid resistance: 0
Strong bases: 0
Ozone - and weather resistance: +
Abrasion: -

Recommendation:

Available Dimensions:

Thickness	Width/Length:	Format:
03-10 mm	1,25 x 10 m	roll

General Information:

Surface grain-textured
Friction coefficient: min. 0,92*

at 3, 5, 6, 8, 10, 12mm thickness

Friction partners: Euro pallet, non slip floor, dry

(acc. VDI 2700 Blatt 14)

*tested value

Legend for recommendation of chemical resistance:

++ = excellent; + = acceptable; 0 = moderately; - = non resistant

** The information, figures, test values and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operation conditions influence the application of each product, the information supplied can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether specified properties of our products are sufficient for the intended use. The use of our products is at the user's own risk. We do not have any influence concerning the application and individual usage.