

Technical Data Sheet

Regenerat Freight Secure

Recycled rubber anti-slip mat (garnules bonded with polyurethane)
According to load securing requirements
Maximum load: 250 t /m² 8 mm thickness

Technical Data*:

Colour: black with multicoloured speckles
Density: 1
Tensile strength: 0,6 N/ mm²
Elongation: 60%
Temperature range: -30° - +100° C

*approximately

Chemical Resistance:

Oil resistance: -
Benzine resistance: -
Acid resistance: **0**
Strong bases: **0**
Ozone - and weather resistance: +
Abrasion: -

Recommendation:

Available Dimmensions:

Thickness	Width/Length:	Format:
03-10 mm	1,25 x 10 m	roll
12-20 mm	1,25 x 5 m	

General Information:

Surface grain-textured

Friction coefficient: min. 0,81*

at 3,4,5,6,8,10,12,15,18,20mm thickness

Friction partners: Euro pallet, non slip floor, dry

(acc. VDI 2700 Blatt 14)

*tested value

Legend for recommendation of chemical resistance:

++ = excellent; + = acceptable; 0 = moderately; - = non resistant

** The information, figures, test values and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operation conditions influence the application of each product, the information supplied can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether specified properties of our products are sufficient for the intended use. The use of our products is at the user's own risk. We do not have any influence concerning the application and individual usage.